

- Note**
- Ask an authorised Daikin dealer to install Daikin products. Do not try to install the product yourself or get it installed by any unauthorised dealer. Improper installation can result in water or refrigerant leakage, electrical shock, fire or explosion. Warranty of the product shall be void if not installed by an authorised Daikin dealer.
 - Use only those parts and accessories supplied or specified by Daikin. Ask authorised Daikin dealer for any repairs or components. Warranty of the product / component shall be void if non specified spares are used or repaired by a non Daikin dealer.
 - Please ensure to install ELCB (Earth Leakage Circuit Breaker) for outdoor units to prevent ground fault effects.

For any inquiries, either call the numbers mentioned below or contact your nearer Daikin dealer.

Cautions on product corrosion

1. Air conditioners should not be installed in areas where corrosive gases, such as acid gas or alkaline gas, are produced.
2. If the outdoor unit is to be installed close to the sea shore, direct exposure to the sea breeze should be avoided. If you need to install the outdoor unit close to the sea shore, contact your local distributor.



JMI-0107

Organization:
DAIKIN INDUSTRIES, LTD.
AIR CONDITIONING MANUFACTURING DIVISION

Scope of Registration:
THE DESIGN/DEVELOPMENT AND MANUFACTURE OF COMMERCIAL AIR CONDITIONING, HEATING, COOLING, REFRIGERATING EQUIPMENT, HEATING EQUIPMENT, RESIDENTIAL AIR CONDITIONING EQUIPMENT, HEAT RECLAIM VENTILATION, AIR CLEANING EQUIPMENT, COMPRESSORS AND VALVES.



JQA-1452

Organization:
DAIKIN INDUSTRIES
(THAILAND) LTD.

Scope of Registration:
THE DESIGN/DEVELOPMENT AND MANUFACTURE OF AIR CONDITIONERS AND THE COMPONENTS INCLUDING COMPRESSORS USED FOR THEM



EC99J2044

All of the Daikin Group's business facilities and subsidiaries in Japan are certified under the ISO 14001 international standard for environment management.

DAIKIN AIRCONDITIONING INDIA PVT. LTD.

12th Floor, Building No. 9, Tower A, DLF Cyber City, DLF Phase III, Gurgaon - 122 002, Haryana, India.
Tel.: 0124-4555444, Fax.: 0124-4555333, e-mail: ho@daikinindia.com

SALES & SERVICE OFFICES

Ahmedabad - Tel.: 079-26583013-14, 36583364
Bengaluru - Tel.: 080-25590452-54
Chandigarh - Tel.: 0172-5089862-64
Chennai - Tel.: 044-24314210-15
Delhi - NCR - Tel.: 0124-4555444
Hyderabad - Tel.: 040-39134293

Jaipur - Tel.: 0141-2223215, 2225569
Kolkata - Tel.: 033-22894259/60
Lucknow - Tel.: 0522-2787307/340/291
Mumbai - Tel.: 022-30926666
Pune - Tel.: 020-25560300



Visit us at www.daikinindia.com

• The specifications, designs, and information in this brochure are subject to change without notice.

Visit us at www.daikinindia.com

DAIKIN

DAIPL-25A

Shaping air to your needs

VRV III-S

THE INTELLIGENT AIR CONDITIONING SYSTEM



A special air conditioning system designed for small offices and shops

COOLING ONLY HEAT PUMP

R-410A

The ideal air conditioning system for small offices and shops

Extending the core “5S” concept—Space saving, Sufficient capacity, Slim design, Sound-reduced operation and Single phase power supply—Daikin’s VRVIII-S offers added value with the “1E” concept—Easy installation. With all these features and more, we proudly present the ideal air conditioning system designed for small-sized buildings.

Slim, compact and sufficient capacity

The VRVIII-S is highly space saving, featuring slim and compact outdoor units. It is suitable for small offices and shops with capacities of 4, 5 and 6 HP.

Volume
Approx. **50%**
reduction



The 5S+1E concepts of
VRVIII-S



5S
concept

- Space saving
- Sufficient capacity
- Slim design
- Sound-reduced operation
- Single phase power supply



Easy installation

1E
concept



Outdoor unit can be installed on a balcony

The compact, trunk-shaped outdoor unit can easily be installed on a balcony, realising complete system installation within each floor. This enables more useful utilisation of the space on the building rooftop.

Contents

Introduction.....	page 1	Indoor unit lineup.....	page 15	Option list.....	page 33
Main features.....	page 3	Specifications.....	page 25	└ Indoor units.....	page 33
Control systems...	page 9	└ Indoor units.....	page 25	└ Outdoor units.....	page 35
		└ Outdoor units.....	page 32	└ Control systems...	page 35

Wide range of choices

To suit the variety of rooms found in small offices and shops, the VRV8-S system offers wide range of indoor and outdoor units.

VRV8-S indoor and outdoor units are almost as easy to install as residential air conditioning systems, making them ideal for small offices and shops.

Outdoor units 3 models

Outdoor unit can be selected from three models to provide the power that suits your needs. The trunk-shaped outdoor unit can be neatly installed outside the office.



Outdoor unit lineup

Model Name	RX(Y)MQ4PVE	RX(Y)MQ5PVE	RX(Y)MQ6PVE
Capacity Range	4 HP (11.2 kW)	5 HP (14.0 kW)	6 HP (15.5 kW)
Capacity Index	100	125	140



Indoor units

14 types 71 models*

A wide range of indoor units includes 71 models in 14 types. The indoor units can be selected to match every room and preference.



Indoor unit lineup 14 types 71 models*

Type	Model Name	Capacity Range	20	25	32	40	50	63	80	100	125	140
			0.8 HP	1 HP	1.25 HP	1.6 HP	2 HP	2.5 HP	3.2 HP	4 HP	5 HP	6 HP
		Capacity Index	20	25	31.25	40	50	62.5	80	100	125	140
Ceiling Mounted Cassette (Round Flow)	FXFQ-LU			●	●	●	●	●	●	●	●	●
Ceiling Mounted Cassette (Compact Multi Flow)	FXZQ-MVE		●	●	●	●	●					
Ceiling Mounted Cassette (Double Flow)	FXCQ-MVE		●	●	●	●	●	●	●		●	
Ceiling Mounted Cassette Corner	FXKQ-MAVE			●	●	●		●				
Slim Ceiling Mounted Duct	FXDQ-PBVE (with drain pump)		●	●	●							
	FXDQ-NBVE (with drain pump)					●	●	●				
Ceiling Mounted Duct	FXMQ-PVE		●	●	●	●	●	●	●	●	●	●
Ceiling Suspended	FXHQ-MAVE				●			●		●		
Wall Mounted	New FXAQ-PVE		New	New	New	New	New	New				
Floor Standing	FXLQ-MAVE		●	●	●	●	●	●				
Concealed Floor Standing	FXNQ-MAVE		●	●	●	●	●	●				

Note: R-410A VRV system indoor units are not compatible with the R-22 VRV system.

Connection unit series indoor units (50 Hz only)

Type	Model Name	Capacity Range	0.8 HP	1 HP	1.25 HP	1.6 HP	2 HP	3 HP	4 HP	5 HP	
			Capacity Index	20	25	31.25	40	50	71	100	125
		Connection Unit							BEV071MAVE	BEV100MAVE	BEV125MAVE
Ceiling Suspended Cassette	FXUQ-MAV1							●	●	●	

Note: BEV units are necessary for Connection unit series indoor units.

Energy efficiency and quiet operation

Outdoor units use Daikin's unique scroll compressor to realise energy saving performance and quiet operation.

High COP during both cooling and heating operations

One of the top features of the VRVIII-S is its energy efficiency. It achieves high COP during cooling and heating operations by employing Daikin's unique scroll compressor.

High COP achieved in all ranges!

		VRVII-S Previous model RXYM-MVM	VRVIII-S
Cooling	4 HP	3.65	3.67
	5 HP	3.28	3.41
	6 HP	2.92	3.36
Heating	4 HP	3.68	3.73
	5 HP	3.41	3.80
	6 HP	3.19	3.63

Above values are based on the following nominal conditions:
 • 2 Ceiling Mounted Cassette (Round Flow) type units are connected (4 HP: FXFQ50P x 2; 5 HP: FXFQ63P x 2; and 6 HP: FXFQ63P + FXFQ80P.)
 • Cooling: Indoor temp. of 27CDB, 19CWB, and outdoor temp. of 35CDB.
 • Heating: Indoor temp. of 20CDB, and outdoor temp. of 7CDB, 6CWB.

Quiet operation provides luxurious comfort

Quietness is yet another important feature of Daikin's VRVIII-S system. To reduce noise and realise comfortable operation, latest technologies and features are applied to the outdoor units.

Lower operation sound is achieved in cooling operation!

1 dB(A) reduced in each model!

		VRVII-S Previous model RXYM-MVM	VRVIII-S
Cooling	4 HP	51	50
	5 HP	52	51

Nighttime quiet operation function

Operation sound level selectable from 3 steps for the night mode

Mode 1. Automatic mode

Set on the outdoor PCB. Time of maximum temperature is memorised. The low operating mode will become active 8 hours*1 after the peak temperature in the daytime, and operation will return to normal 10 hours*2 after that. The operation sound level for the night mode can be selected from 47 dB(A) (Step 1), 44 dB(A) (Step 2) and 41 dB(A) (Step 3).


Mode 2. Manual mode

Starting time and ending time can be input. (An external control adaptor for outdoor unit, DTA104A61 or DTA104A62, and a locally obtained timer are necessary.)

Mode 3. Combined mode

Combinations of modes 1 and 2 can be used depending on your needs.

*1. Initial setting. Can be selected from 6, 8 and 10 hours.
 *2. Initial setting. Can be selected from 8, 9 and 10 hours.




Note: • This function is available in setting at site.
 • The relationship of outdoor temperature (load) and time shown in the graph is just an example.
 * The capacity reduction rate differs depending on the operation sound level step selected.

A collection of cutting-edge technologies realises efficient and quiet operation.

The high efficiency compressor to achieve a higher COP


1 Compressor equipped with Reluctance DC motor

Daikin DC inverter models are equipped with the Reluctance DC motor for compressor. The Reluctance DC motor uses 2 different types of torque, neodymium magnet*1 and reluctance torque*2. This motor can save energy because it generates more power with a smaller electric power than an AC or conventional DC motor.




Note: Data are based on studies conducted under controlled conditions at a Daikin laboratory using Daikin products.

*1 A neodymium magnet is approximately 10 times stronger than a standard ferrite magnet.
 *2 The torque created by the change in power between the iron and magnet parts.



RX(Y)MQ4PVE
 RX(Y)MQ5PVE
 RX(Y)MQ6PVE



>> Smooth sine wave DC inverter

Use of an optimised sine wave smoothes motor rotation, further improving operating efficiency.

Sine wave DC inverter




2 Smooth Air Inlet Bell Mouth and Aero Spiral Fan

These two features work to reduce sound. Guides are added to the bell mouth intake to reduce turbulence in the airflow generated by fan suction. The Aero Spiral Fan features fan blades with the bent blade edges, further reducing turbulence.



With the bent blade edge Without the bent blade edge




Escaping eddies are sucked in by the bent blade edges, reducing overall turbulence.

3 DC fan motor

Efficiency improved in all areas compared to conventional AC motors, especially at low speeds.

DC fan motor structure



Note: Data are based on studies conducted under controlled conditions at a Daikin laboratory.

Design flexibility


VRVIII-S systems offer broad design flexibility with long refrigerant piping lengths and multiple indoor unit combinations, which provides generous freedom for office and shop design both inside and out.

As many as 9 indoor units can be connected to a single outdoor unit

Multiple indoor unit combinations are possible.* As many as 9 indoor units can be connected to a single outdoor unit, making the VRVIII-S a remarkably versatile system.


* Total capacity index of connectable indoor units must be 50 - 130 % of the capacity index of the outdoor unit.

For a 6 HP installation



Long piping design possible

The VRVIII-S provides the long piping length possibility of 150 m, with a total piping length of 300 m. If the outdoor unit is installed above indoor units the level difference can be up to a maximum of 50 m. These generous allowances facilitate an extensive variety of system designs.




Actual piping length
Max. 150 m

Total piping length
Max. 300 m

Notes: *1. 40 m when the outdoor unit is installed below indoor units.
*2. Maximum piping length between the indoor unit and the first branch is 40 m.

Wide operation temperature range

The versatile operation range of the VRVIII-S system works to reduce limitations on installation locations. The operation temperature range for heating goes all the way down to -20C, while cooling can be performed with outdoor temperatures as high as 46C. Both these achievements are due to the adoption of a high-pressure dome-type compressor.




Easy installation

A variety of functions are provided that make installation easier, such as simple wiring and piping and automatic test operation.

Easy wiring

A printed circuit board has been adopted that is easy to see and wire during installation.



Automatic test operation


Simply press the test operation button and the unit performs an automatic system check, including wiring, shutoff valves, and sensors. The results are returned automatically after the check finishes.

Simple wiring and piping connection

Unique piping and wiring systems make it possible to install a VRVIII-S system quickly and easily.


>> Super wiring system

A super wiring system is used to enable shared use of the wiring between indoor and outdoor units and the central control wiring, with a relatively simple wiring operation. The DIII-NET communication system is employed to enable the use of advanced control systems.



>> REFNET piping system

Daikin's advanced REFNET piping system makes installation easy. Only two main refrigerant lines are required in any one system. REFNET greatly reduces the imbalances in refrigerant flow between units, while using small-diameter piping.



Control systems

The VRVIII-S system uses the same DIII-NET communication system as the VRV, enabling the use of advanced control systems.

Individual control systems

Navigation remote controller (Wired remote controller) (Option)



BRC1E61

- Large buttons and arrow keys for easy operation.
- Guide on display gives an explanation of each setting.
- Backlight and dot matrix LCD display for easy viewing.
- Weekly schedule timer can be set up easily.
- 10 display languages are available. (English, German, French, Spanish, Italian, Portuguese, Greek, Dutch, Russian and Turkish)

Wired remote controller (Option)

Displays current airflow, swing, temperature, operating mode and timer settings.



BRC1C62

Wired remote controller with weekly schedule timer (Option)


Adds weekly schedule timer function.



BRC1D61

Notes: 1. Standard remote controllers (BRC1C62) not required.
2. If the BRC1D61 is connected to the centralised remote controllers (DCS303A51, DCS302CA61, DCS301BA61, DST301BA61), the schedule function is not available.

The wired remote controller supports a wide range of control functions



*Refer to page 7 for the total number of indoor units that can be connected to the outdoor unit.

Wireless remote controller (Option)




Wireless remote controller

Signal receiver unit (Separate type)

- The same operation modes and settings as with wired remote controllers are possible.
- A compact signaling is included.
 - A signallow, Compact Multi Flow, Double Flow) type, Ceiling Suspended type and Wall Mounted type is mounted into the indoor unit.



Signal receiver unit can be installed on the panel ex. Ceiling Mounted Cassette (Round Flow) type



Signal receiver unit (Installed type)

*Wireless remote controller and unit are sold as a set.
*Refer to page 35 for the name of each model.

Simplified (Option)



Exposed type (BRC2C51)

Concealed type (For hotel use) (BRC3A61)

- The remote controller has centralised its frequently used operation selectors and switches (on/off, operation mode, temperature setting and airflow volume), making itself suitable for use in hotel rooms or conference rooms.
- The exposed type remote controller is fitted with a thermostat sensor.



The concealed type remote controller smartly fits into a night table or console panel in a hotel room.

Wide variation of remote controllers for indoor units

	FXFQ	FXZQ	FXCQ	FXKQ	FXDQ	FXMQ	FXHQ	FXAQ	FXL(N)Q	FXUQ
Navigation remote controller (Wired remote controller) (BRC1E61)	●	●	●	●	●	●	●	●	●	●
Wired remote controller (BRC1C62)	●	●	●	●	●	●	●	●	●	●
Wired remote controller with weekly schedule timer (BRC1D61)	●	●	●	●	●	●	●	●	●	●
Wireless remote controller* (Installed type)	●	●	●				●	●		●
Wireless remote controller* (Separate type signal receiver unit)				●	●	●			●	
Simplified remote controller (Exposed type) (BRC2C51)					●	●			●	
Simplified remote controller (Concealed type: for Hotel use) (BRC3A61)					●	●			●	

*Refer to page 35 for the name of each model.

Centralised control systems

- Up to 64 groups of indoor units (128 units) can be centrally controlled.
- Optional controllers for centralised control can be combined and optimised in accordance with building scale and purpose.
- System integration with various air-conditioning peripheral equipment such as Heat Reclaim Ventilator is easy.
- Wiring can be run up to a total length of 2 km, and adapts easily to large-scale system expansion.

Residential central remote controller* (Option)



DCS303A51

Max. 16 groups of indoor units can be easily controlled with the large LCD panel.

- Max. 16 groups (128 indoor units) controllable
- Backlight and large LCD panel for easy readability
- ON/OFF, temperature settings and scheduling can be controlled individually for indoor units.
- All indoor units can be turned on or off at once with "ALL" button.
- Each group has a dedicated button for convenience.
- Outside temperature display

*For residential use only. Cannot be used with other centralised control equipment.

Central remote controller (Option)



DCS302CA61

Max. 64 groups (zones) of indoor units can be controlled individually same as LCD Remote controller.

- Max. 64 groups (128 indoor units) controllable
- Max. 128 groups (128 indoor units) are controllable by using 2 central remote controllers, which can control from 2 different places.
- Zone control
- Malfunction code display
- Max. wiring length 1,000 m (Total: 2,000 m)
- Connectable with Unified ON/OFF controller, schedule timer and BMS system
- Airflow volume and direction can be controlled individually for indoor units in each group operation.
- Ventilation volume and mode can be controlled for Heat Reclaim Ventilator.
- Up to 4 ON/OFF pairs can be set per day by connecting a schedule timer.

Unified ON/OFF controller (Option)



DCS301BA61

Max. 16 groups of indoor units can be operated simultaneously/individually.

- Max. 16 groups (128 indoor units) controllable
- 2 remote controllers can be used to control from 2 different places.
- Operating status indication (Normal operation, Alarm)
- Centralised control indication
- Max. wiring length 1,000 m (Total: 2,000 m)
- Compact size casing (Thickness: 16 mm)
- Connectable with Central Remote controller, Schedule timer and BMS system


Schedule timer (Option)



DST301BA61

Max. 128 indoor units can be operated as programmed schedule.

- Max. 128 indoor units controllable
- When used in combination with a central remote controller, a maximum of 8 weekly schedule patterns can be set, while the central controller can be used to select desired zones. Up to 2 ON/OFF pairs can be set per day.
- Max. 48 hours back up power supply
- Max. wiring length 1,000 m (Total: 2,000 m)
- Compact size casing (Thickness: 16 mm)
- Connectable with Central Remote controller, Unified ON/OFF controller and BMS system



*1. Refer to page 7 for the total number of indoor units that can be connected to the outdoor unit.
 • Certain indoor units limit the functions of some control systems.


Advanced control systems



One touch selection to total air comfort

Daikin proudly introduces its new *intelligent Touch Manager*, a VRV system controller featuring an array of simple, useful system management functions for added value.

Up to 2,560 groups (5,120 indoor units) can be controlled by one system




Features

- ★ **Central control**
 - Handy area settings simplify detailed management of VRV.
 - Display of floor plans enables a quick search of desired air conditioning units.
 - Operation history shows manner of control and origin in past operations of air conditioning units.
- ★ **Remote access**
 - Remote access with a PC allows total air conditioning management using the same type of screens as those displayed in the *intelligent Touch Manager*.
 - Authorised users can centrally control individual air conditioning units from their own computers.
- ★ **Automatic control**
 - VRVs are controlled automatically throughout the year by the schedule function.
 - Interlocking VRVs and other equipment enables easy automation of building facilities operation.
 - Setback adjusts temperature settings even when rooms are unoccupied.
- ★ **Energy management**
 - The Energy Navigator feature simplifies energy management by tracking energy consumption data and identifying inefficient operation.
- ★ **Troubleshooting**
 - Contact information of maintenance contractors can be registered and displayed.
 - E-mails are sent automatically to alert of malfunctions and potential trouble.
 - The *intelligent Touch Manager* can link to the Air Conditioning Network Service System for 24-hour monitoring of operating conditions and status.
- ★ **Scalability**
 - A single *intelligent Touch Manager* can manage a small building or be expanded to handle medium- to large-sized buildings.
 - Large building properties can also take advantage of the *iTM integrator* to link up and expand system up to 5 *intelligent Touch Managers* for integrated control.



Communication functions in the user-friendly icon-based multilingual controller simplify centralised control of the VRV system.



Features

- Colour LCD touch panel icon display
- Small manageable size
- Simplified engineering
- Multi language (English, French, Italian, German, Spanish, Dutch, Portuguese, Chinese and Korean)
- Yearly schedule
- Auto heat/cool change-over
- Temperature limitation
- Enhanced history function
- Simple Interlock Function
- Built-in modem for connecting to Air Conditioning Network Service System (Option)
- Doubling of number of connectable indoor units by adding a DIII-NET Plus Adaptor (Option)
- Management of facilities/equipment other than A/C units (By adding Dio unit or Di unit)




Ceiling Mounted Cassette (Round Flow) Type

FXFQ25L/FXFQ32L/FXFQ40L
FXFQ50L/FXFQ63L/FXFQ80L
FXFQ100L/FXFQ125L



360 airflow improves temperature distribution and offers a comfortable living environment.


- The industry's first* Round Flow Ceiling Mounted Cassette type offers 360 airflow with improved temperature distribution.



*As of April 2004, the release date for Japan.

- All models are lighter than the conventional ones. Ex: Models FXFQ25L-50L are 4.5 kg lighter (reduced from 24 kg to 19.5 kg).

- Drain pump is equipped as standard accessory, and the lift height has been improved from 750 mm to 850 mm.



- A modern sophisticated decoration panel has been applied, with a panel surface that has been treated with a dirt-repellant coating.



- Control of the airflow rate has been improved from 2-step to 3-step control.

Low operation sound level (dB(A))

FXFQ-L	25/32	40	50	63	80	100	125
Sound level (H/L)	30/28.5/27	31/29/27	32/29.5/27	34/31/28	36/33.5/31	43/37.5/32	44/39/34

- Example of airflow patterns: 360 airflow is available, as well as 2- to 4-way flows, so you can choose the most suitable airflow pattern depending on location or room layout.



- An antibacterial treatment that uses silver ions has been applied to the drain pan, preventing the growth of slime, mould and bacteria that cause blockages and odours.

- The horizontal louvres prevent dew condensation. Their non-flocking surfaces, which repel dirt, are easy to clean.

- The air filter has an anti-mould and antibacterial treatment that prevents the growth of mould generated from dust or moisture that may adhere to the filter.

Ceiling Mounted Cassette (Compact Multi Flow) Type

FXZQ20M/FXZQ25M
FXZQ32M/FXZQ40M
FXZQ50M



Quiet, compact, and designed for user comfort


- Dimensions correspond with 600 mm x 600 mm architectural module ceiling design specifications.

- Low operation sound level

FXZQ-M		20/25	32	40	50
Sound level (H/L)	230 V	30/25	32/26	36/28	41/33
	240 V	32/26	34/28	37/29	42/35


- Comfortable airflow

- Wide discharge angle: 0 to 60



*Angles can be also set on site to prevent drafts (0-35) or soiling of the ceiling (25-60), other than standard setting (0-60).


- 2-, 3-, and 4-way airflow patterns are available, enabling installation in the corner of a room.



*For 3-way or 2-way flow installation, the sealing member for air discharge outlet (option) must be used to close each unused outlet.



- Drain pump is equipped as standard accessory with 750 mm lift.



Note: Whatever the discharge direction, the same type of panel is used. If installing for other than all-round flow, an air discharge outlet sealing member (option) must be used to close each unused outlet.


Ceiling Mounted Cassette (Double Flow) Type

FXCQ20M/FXCQ25M/FXCQ32M
FXCQ40M/FXCQ50M/FXCQ63M
FXCQ80M/FXCQ125M



Thin, lightweight, and easy to install in shallow ceiling spaces

- The low profile unit (only 305 mm high) can be installed in a ceiling space as shallow as 350 mm. All models feature a compact design with a depth of only 600 mm.



(When a high-efficiency filter is attached, the unit's height is 400 mm.)


- Low operation sound level (dB(A))

FXCQ-M	20	25/32	40/50	63	80	125
Sound level (H/L)	220 V 32/27	34/28	34/29	37/32	39/34	44/38
	240 V 34/29	36/30	37/32	39/34	41/36	46/40

- Designed with higher airflow suitable for high ceiling application up to 3 metres.

- Providing 2 different settings of standard and ceiling soiling prevention, the auto swing mechanism achieves even distribution of airflow and room temperature.

- Drain pump is equipped as standard accessory with 600 mm lift.



- Two types of optional high-efficiency filter are available (65% and 95%, colourimetric method).

- A long-life filter (maintenance free up to one year*) is equipped as standard accessory.

*8 hr/day, 25 day/month. For dust concentration of 0.15 mg/m³

- Major maintenance work can be performed by removing the panel. A flat-type suction grille and a detachable blade make cleaning easy.


Ceiling Mounted Cassette Corner Type

FXKQ25MA/FXKQ32MA
FXKQ40MA/FXKQ63MA



Slim design for flexible installation

- Slim body needs only 220 mm space above the ceiling. If you use a panel spacer (option), the unit can be installed in the minimum space of 195 mm.




- Single-flow type allows effective air discharge from corner or from drop-ceiling.


- Drain pump is equipped as standard accessory with 500 mm lift.




- Providing 3 different settings of standard, draft prevention and ceiling soiling prevention, the auto swing mechanism achieves even distribution of airflow and room temperature.



- Front discharge is possible with an air discharge unit (option), which allows the installation in the drop-ceiling or sagging wall.



*Set for front discharge using a suspended ceiling.



*Downward discharge is shut off and air is blown straight out (front discharge).

- A long-life filter (maintenance free up to one year*) is equipped as standard accessory.

*8 hr/day, 25 day/month. For dust concentration of 0.15 mg/m³



Slim Ceiling Mounted Duct Type



Slim design, quietness and static pressure switching

Ceiling Mounted Duct Type




FXMQ20P/FXMQ25P/FXMQ32P
FXMQ40P/FXMQ50P/FXMQ63P
FXMQ80P/FXMQ100P/FXMQ125P
FXMQ140P

Suited to use in drop-ceilings!

FXDQ20PB/FXDQ25PB/FXDQ32PB


- Only 700 mm in width and 23 kg in weight, this model is suitable to install in limited spaces like drop-ceilings in hotels.

Great for hotel use!




FXDQ40NB/FXDQ50NB/FXDQ63NB

- Only 200 mm in height, this model can be installed in rooms with as little as 240 mm depth between the drop-ceiling and ceiling slab.



* 1,100 mm in width for the FXDQ63NB model.




- External static pressure selectable by remote controller switching make this indoor unit a very comfortable and flexible model.

10 Pa-30 Pa/factory set: 10 Pa for FXDQ-PB models.
15 Pa-44 Pa/factory set: 15 Pa for FXDQ-NB models.

- FXDQ-PB and FXDQ-NB models are available in two types to suit different installation conditions.

FXDQ-PB/NBVE: with a drain pump (750 mm lift) as a standard accessory



Middle and high static pressure allows for flexible duct design


- A DC fan motor increases the external static pressure capacity range to include middle to high static pressures, increasing design flexibility.

30 Pa-100 Pa for FXMQ20P-32P
30 Pa-160 Pa for FXMQ40P
50 Pa-200 Pa for FXMQ50P-125P
50 Pa-140 Pa for FXMQ140P

- All models are only 300 mm in height, an improvement over the 390 mm height of conventional models. The weight of the FXMQ40P has been reduced from 44 kg to 28 kg.



- Drain pump is equipped as standard accessory with 700 mm lift.




- Control of the airflow rate has been improved from 2-step to 3-step control.

- Low operation sound level

FXMQ-P	20/25	32	40	50	63	80/100	125	140
Sound level (HH/H/L)	33/31/29	34/32/30	39/37/35	41/39/37	42/40/38	43/41/39	44/42/40	46/45/43

- Energy-efficient

- The adopted DC fan motor is much more efficient than the conventional AC motor, yielding an approximate 20% decrease in energy consumption. (FXMQ125P)



- Improved ease of installation

- Airflow rate can be controlled using a remote controller during test operation. conventional model, the airflow rate was controlled from the PC board. It is automatically adjusted to the range between approximately 10% of the rated HH tap airflow for FXMQ20P-125P.

- Improved ease of maintenance

- The drain pan can be detached for easy cleaning. An antibacterial treatment that uses silver ions has been applied to the drain pan, preventing the growth of slime, mould and bacteria that cause blockages and odours.



- Control of the airflow rate has been improved from 2-step to 3-step control.

- Low operation sound level

FXDQ-PB/NB	20/25/32	40	50	63
Sound level (HH/H/L)	33/31/29	34/32/30	35/33/31	36/34/32

*The values of operation sound level represent those for rear-suction operation. Sound level values for bottom-suction operation can be obtained by adding 5 dB(A).
*Values are based on the following conditions:
FXDQ-PB: external static pressure of 10 Pa; FXDQ-NB: external static pressure of 15 Pa.

Ceiling Suspended Type


FXHQ32MA/FXHQ63MA
FXHQ100MA



Slim body with quiet and wide airflow

Adoption of QUIET STREAM FAN

Uses the quiet stream fan and many advanced technologies.




Low operation sound level


FXHQ-MA	32	63	100
Sound level (H/L)	36/31	39/34	45/37

Installation is easy

- Drain pump kit (option) can be easily incorporated.




- Wide air discharge openings produce a spreading 100 airflow.



Maintenance is easy

- Non-dew Flap with no implanted bristles
Bristle-free Flap minimises contamination and makes cleaning simpler.
- Easy-to-clean flat design
- Maintenance is easier because servicing can be performed from below the unit.
- A long-life filter (maintenance free up to one year) is equipped as standard accessory.



Wall Mounted Type

New

FXAQ20P/FXAQ25P
FXAQ32P/FXAQ40P
FXAQ50P/FXAQ63P



Stylish flat panel design harmonised with your interior décor

- Stylish flat panel design creates a graceful harmony that enhances any interior space.

- Flat panel can be cleaned with only the single pass of a cloth across their smooth surface. Flat panel can also be easily removed and washed for more thorough cleaning.

Low operation sound level

FXAQ-P	20	25	32	40	50	63
Sound level (H/L)	35/31	36/31	38/31	39/34	42/37	47/41

- Drain pan and air filter can be kept clean by mould-proof polystyrene.

- Vertical auto-swing realises efficiency of air distribution. The louvre closes automatically when the unit stops.

- 5 steps of discharge angle can be set by remote controller.


- Discharge angle is automatically set at the same angle as the previous operation when restarting. (Initial setting: 10° for cooling and 70° for heating)

Flexible installation

- Drain pipe can be fitted to from either left or right sides.



- Drain pump kit is available as optional accessory, which lifts the drain 1,000 mm from the bottom of the unit.




Floor Standing Type

FXLQ20MA/FXLQ25MA
FXLQ32MA/FXLQ40MA
FXLQ50MA/FXLQ63MA



Suitable for perimeter zone air conditioning

- Floor Standing types can be hung on the wall for easier floor cleaning. Running the piping from the back allows the unit to be hung on walls. Cleaning under the unit, where dust tends to accumulate, is considerably easier.
- The adoption of a fibre-less discharge grille featuring an original design to prevent condensation also helps prevent staining and makes cleaning easier.
- A long-life filter (maintenance free up to one year*) is equipped as standard accessory.
*8 hr/day, 25 day/month. For dust concentration of 0.15 mg/m³




Concealed Floor Standing Type

FXNQ20MA/FXNQ25MA
FXNQ32MA/FXNQ40MA
FXNQ50MA/FXNQ63MA



Designed to be concealed in the perimeter skirting-wall

- The unit is concealed in skirting-wall of perimeter, that enables to create high class interior design.
- The connecting port faces downward, greatly facilitating on-site piping work.
- A long-life filter (maintenance free up to one year*) is equipped as standard accessory.
* Applies also to Floor Standing type (FXLQ-MA).
*8 hr/day, 25 day/month. For dust concentration of 0.15 mg/m³



Connection unit series indoor units


Ceiling Suspended Cassette Type (50 Hz only)

FXUQ71MA
FXUQ100MA
FXUQ125MA




This thin indoor unit achieves optimum air distribution, and can be installed without the need for ceiling cavity

- Depending on installation site requirements or room conditions, 2-way, 3-way and 4-way discharge patterns are available.



Connection unit Connection unit is the device for connecting above indoor unit to VRVIII-S.

BEVQ71MA/BEVQ100MA/BEVQ125MA



Model	Maximum piping length between the BEV unit and the indoor unit.
FXUQ-MA	5 m

- Notes:**
- When connecting centralised-control device, it is necessary to install an interface adaptor for an indoor unit (DTA102A52).
 - Connection unit BEVQ-MA is necessary for each indoor unit.
 - The refrigerant piping height difference between the indoor units and the BEV unit must be within 4 m.
 - The BEV unit must be installed within a maximum height difference between indoor units of 15 m.
 - Branching of the refrigerant piping is not possible downstream of the BEV unit.

SPECIFICATIONS

INDOOR UNITS

Ceiling Mounted Cassette (Round Flow) Type



MODEL		FXFQ25LU	FXFQ32LU	FXFQ40LU	FXFQ50LU	FXFQ63LU	FXFQ80LU	FXFQ100LU	FXFQ125LU	
Power supply		1-phase, 220-240 V/220 V, 50 Hz								
Cooling capacity	kcal/h (*1)	2,500	3,200	4,000	5,000	6,300	8,000	10,000	12,500	
	Btu/h (*1)	9,900	12,600	16,000	19,800	24,900	31,700	39,600	49,500	
	kW	(*1)	2.9	3.7	4.7	5.8	7.3	9.3	11.6	14.5
		(*2)	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0
Heating capacity	kcal/h	2,800	3,400	4,300	5,400	6,900	8,600	10,800	13,800	
	Btu/h	10,900	13,600	17,100	21,500	27,300	34,100	42,700	54,600	
	kW	3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0	
Casing		Galvanised steel plate								
Airflow rate (HH/H/L)	m ³ /min	13/11.5/10	13/11.5/10	15/13/11	16/13.5/11	19/16.5/13.5	21/18/15	32/26/20	33/28/22.5	
	cfm	459/406/353	459/406/353	530/459/388	565/477/388	671/583/477	742/636/530	1,130/918/706	1,165/989/794	
Sound level (HH/H/L)	dB(A)	30/28.5/27	30/28.5/27	31/29/27	32/29.5/27	34/31/28	36/33.5/31	43/37.5/32	44/39/34	
Dimensions (H×W×D)	mm	246×840×840	246×840×840	246×840×840	246×840×840	246×840×840	246×840×840	288×840×840	288×840×840	
Machine weight	kg	19.5	19.5	19.5	19.5	22	22	25	25	
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 6.4	φ 6.4	φ 6.4	φ 9.5	φ 9.5	φ 9.5	
	Gas (Flare)	mm	φ 12.7	φ 12.7	φ 12.7	φ 12.7	φ 15.9	φ 15.9	φ 15.9	
	Drain	VP25 (External Dia, 32/Internal Dia, 25)								
Panel (Option)	Model	BYCP125K-W1								
	Colour	Fresh white								
	Dimensions (H×W×D)	mm	50X950X950	50X950X950	50X950X950	50X950X950	50X950X950	50X950X950	50X950X950	
	Weight	kg	5.5	5.5	5.5	5.5	5.5	5.5	5.5	


Ceiling Mounted Cassette (Compact Multi Flow) Type



MODEL		FXZQ20MVE	FXZQ25MVE	FXZQ32MVE	FXZQ40MVE	FXZQ50MVE	
Power supply		1-phase, 220-240 V/220 V, 50 Hz					
Cooling capacity	kcal/h (*1)	2,000	2,500	3,200	4,000	5,000	
	Btu/h (*1)	7,800	9,900	12,600	16,000	19,800	
	kW	(*1)	2.3	2.9	3.7	4.7	5.8
		(*2)	2.2	2.8	3.6	4.5	5.6
Heating capacity	kcal/h	2,200	2,800	3,400	4,300	5,400	
	Btu/h	8,500	10,900	13,600	17,100	21,500	
	kW	2.5	3.2	4.0	5.0	6.3	
Casing		Galvanised steel plate					
Airflow rate (H/L)	m ³ /min	9/7	9/7	9.5/7.5	11/8	14/10	
	cfm	318/247	318/247	335/265	388/282	493/353	
Sound level (H/L)	dB(A)	30/25-32/26-32/29	30/25-32/26-32/29	32/26-34/28-33/29	36/28-37/29-36/30	41/33-42/35-41/34	
Dimensions (H×W×D)	mm	286×575×575					
Machine weight	kg	18					
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 6.4	φ 6.4	φ 6.4	
	Gas (Flare)	mm	φ 12.7	φ 12.7	φ 12.7	φ 12.7	
	Drain	VP20 (External Dia, 26/Internal Dia, 20)					
Panel (Option)	Model	BYFQ60B8W1					
	Colour	White (6.5Y9.5/0.5)					
	Dimensions (H×W×D)	mm	55×700×700	55×700×700	55×700×700	55×700×700	
	Weight	kg	2.7	2.7	2.7	2.7	

Note: Specifications are based on the following conditions:
 -Cooling: Indoor temp.: (*1)27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m. (*2)27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m. -Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m. -Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre. During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Ceiling Mounted Cassette (Double Flow) Type



MODEL		FXCQ20MVE	FXCQ25MVE	FXCQ32MVE	FXCQ40MVE	FXCQ50MVE	FXCQ63MVE	FXCQ80MVE	FXCQ125MVE	
Power supply		1-phase, 220-240 V/220 V, 50 Hz								
Cooling capacity	kcal/h (*1)	2,000	2,500	3,200	4,000	5,000	6,300	8,000	12,500	
	Btu/h (*1)	7,800	9,900	12,600	16,000	19,800	24,900	31,700	49,500	
	kW	(*1)	2.3	2.9	3.7	4.7	5.8	7.3	9.3	14.5
		(*2)	2.2	2.8	3.6	4.5	5.6	7.1	9.0	14.0
Heating capacity	kcal/h	2,200	2,800	3,400	4,300	5,400	6,900	8,600	13,800	
	Btu/h	8,500	10,900	13,600	17,100	21,500	27,300	34,100	54,600	
	kW	2.5	3.2	4.0	5.0	6.3	8.0	10.0	16.0	
Casing		Galvanised steel plate								
Airflow rate (H/L)	m ³ /min	7/5	9/6.5	9/6.5	12/9	12/9	16.5/13	26/21	33/25	
	cfm	247/177	318/230	318/230	424/318	424/318	582/459	918/741	1,165/883	
Sound level (H/L)	220 V	dB(A)	32/27	34/28	34/28	34/29	34/29	37/32	39/34	
	240 V		34/29	36/30	36/30	37/32	37/32	39/34	41/36	
Dimensions (H×W×D)	mm	305×775×600	305×775×600	305×775×600	305×990×600	305×990×600	305×1,175×600	305×1,665×600	305×1,665×600	
Machine weight	kg	26	26	26	31	32	35	47	48	
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 6.4	φ 6.4	φ 6.4	φ 6.4	φ 9.5	φ 9.5	
	Gas (Flare)	mm	φ 12.7	φ 12.7	φ 12.7	φ 12.7	φ 12.7	φ 15.9	φ 15.9	
	Drain	VP25 (External Dia, 32/Internal Dia, 25)								
Panel (Option)	Model	BYBC32G-W1		BYBC50G-W1		BYBC63G-W1		BYBC125G-W1		
	Colour	White (10Y9/0.5)								
	Dimensions (H×W×D)	mm	53×1,030×680	53×1,030×680	53×1,030×680	53×1,245×680	53×1,245×680	53×1,430×680	53×1,920×680	
	Weight	kg	8.0	8.0	8.0	8.5	8.5	9.5	12.0	

Ceiling Mounted Cassette Corner Type




MODEL		FXKQ25MAVE	FXKQ32MAVE	FXKQ40MAVE	FXKQ63MAVE	
Power supply		1-phase, 220-240 V/220 V, 50 Hz				
Cooling capacity	kcal/h (*1)	2,500	3,200	4,000	6,300	
	Btu/h (*1)	9,900	12,600	16,000	24,900	
	kW	(*1)	2.9	3.7	4.7	7.3
		(*2)	2.8	3.6	4.5	7.1
Heating capacity	kcal/h	2,800	3,400	4,300	6,900	
	Btu/h	10,900	13,600	17,100	27,300	
	kW	3.2	4.0	5.0	8.0	
Casing		Galvanised steel plate				
Airflow rate (H/L)	50 Hz	m ³ /min	11/9	11/9	13/10	
		cfm	388/318	388/318	459/353	
Sound level (H/L)	220 V	dB(A)	38/33	38/33	40/34	
	240 V		40/35	40/35	42/36	
Dimensions (H×W×D)	mm	215×1,110×710	215×1,110×710	215×1,110×710	215×1,310×710	
Machine weight	kg	31	31	31	34	
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 6.4	φ 6.4	
	Gas (Flare)	mm	φ 12.7	φ 12.7	φ 12.7	
	Drain	VP25 (External Dia, 32/Internal Dia, 25)				
Panel (Option)	Model	BYK45FJW1		BYK71FJW1		
	Colour	White (10Y9/0.5)				
	Dimensions (H×W×D)	mm	70×1,240×800	70×1,240×800	70×1,240×800	
	Weight	kg	8.5	8.5	8.5	

Note: Specifications are based on the following conditions:
 -Cooling: Indoor temp.: (*1)27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m. (*2)27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m. -Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m. -Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index. Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre. During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS

Slim Ceiling Mounted Duct Type (700 mm width type)



MODEL	with drain pump	FXDQ20PBVE	FXDQ25PBVE	FXDQ32PBVE	
Power supply		1-phase, 220-240 V/220 V, 50 Hz			
Cooling capacity	kcal/h (*1)	2,000	2,500	3,200	
	Btu/h (*1)	7,800	9,900	12,600	
	kW	(*1)	2.3	2.9	3.7
		(*2)	2.2	2.8	3.6
Heating capacity	kcal/h	2,200	2,800	3,400	
	Btu/h	8,500	10,900	13,600	
	kW	2.5	3.2	4.0	
Casing		Galvanised steel plate			
Airflow rate (HH/H/L)	m ³ /min	8.0/7.2/6.4	8.0/7.2/6.4	8.0/7.2/6.4	
	cfm	282/254/226	282/254/226	282/254/226	
External static pressure	Pa	30-10*1			
Sound level (HH/H/L)*2*3	dB(A)	33/31/29	33/31/29	33/31/29	
Dimensions (H×W×D)	mm	200×700×620	200×700×620	200×700×620	
Machine weight	kg	23	23	23	
Piping connections	Liquid (Flare)	φ 6.4	φ 6.4	φ 6.4	
	Gas (Flare)	φ 12.7	φ 12.7	φ 12.7	
	Drain	VP20 (External Dia, 26/Internal Dia, 20)			

Ceiling Mounted Duct Type



MODEL	FXMQ20PVE	FXMQ25PVE	FXMQ32PVE	FXMQ40PVE	FXMQ50PVE		
Power supply		1-phase, 220-240 V/220 V, 50 Hz					
Cooling capacity	kcal/h (*1)	2,000	2,500	3,200	4,000	5,000	
	Btu/h (*1)	7,800	9,900	12,600	16,000	19,800	
	kW	(*1)	2.3	2.9	3.7	4.7	5.8
		(*2)	2.2	2.8	3.6	4.5	5.6
Heating capacity	kcal/h	2,200	2,800	3,400	4,300	5,400	
	Btu/h	8,500	10,900	13,600	17,100	21,500	
	kW	2.5	3.2	4.0	5.0	6.3	
Casing		Galvanised steel plate					
Airflow rate (HH/H/L)	m ³ /min	9/7.5/6.5	9/7.5/6.5	9.5/8/7	16/13/11	18/16.5/15	
	cfm	318/265/230	318/265/230	335/282/247	565/459/388	635/582/530	
External static pressure	Pa	30-100*1	30-100*1	30-100*1	30-160*1	50-200*1	
Sound level (HH/H/L)	dB(A)	33/31/29	33/31/29	34/32/30	39/37/35	41/39/37	
Dimensions (H×W×D)	mm	300×550×700	300×550×700	300×550×700	300×700×700	300×1,000×700	
Machine weight	kg	25	25	25	28	36	
Piping connections	Liquid (Flare)	φ 6.4	φ 6.4	φ 6.4	φ 6.4	φ 6.4	
	Gas (Flare)	φ 12.7	φ 12.7	φ 12.7	φ 12.7	φ 12.7	
	Drain	VP25 (External Dia, 32/Internal Dia, 25)					

Slim Ceiling Mounted Duct Type (900/1,100 mm width type)



MODEL	with drain pump	FXDQ40NBVE	FXDQ50NBVE	FXDQ63NBVE	
Power supply		1-phase, 220-240 V/220 V, 50 Hz			
Cooling capacity	kcal/h (*1)	4,000	5,000	6,300	
	Btu/h (*1)	16,000	19,800	24,900	
	kW	(*1)	4.7	5.8	7.3
		(*2)	4.5	5.6	7.1
Heating capacity	kcal/h	4,300	5,400	6,900	
	Btu/h	17,100	21,500	27,300	
	kW	5.0	6.3	8.0	
Casing		Galvanised steel plate			
Airflow rate (HH/H/L)	m ³ /min	10.5/9.5/8.5	12.5/11.0/10.0	16.5/14.5/13.0	
	cfm	371/335/300	441/388/353	583/512/459	
External static pressure	Pa	44-15*1			
Sound level (HH/H/L)*2*3	dB(A)	34/32/30	35/33/31	36/34/32	
Dimensions (H×W×D)	mm	200×900×620	200×900×620	200×1,100×620	
Machine weight	kg	27	28	31	
Piping connections	Liquid (Flare)	φ 6.4	φ 6.4	φ 9.5	
	Gas (Flare)	φ 12.7	φ 12.7	φ 15.9	
	Drain	VP20 (External Dia, 26/Internal Dia, 20)			

Note: Specifications are based on the following conditions;

-Cooling: Indoor temp.: (*1) 27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.

(*2) 27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.

-Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.

-Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index.

-Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.

During actual operation, these values are normally somewhat higher as a result of ambient conditions.

* 1: External static pressure is changeable to set by the remote controller. This pressure means "High static pressure - Standard". (Factory setting is 10 Pa for FXDQ-PB models and 15 Pa for FXDQ-NB models.)

* 2: The values of operation sound level represent those for rear-suction operation. Sound level values for bottom-suction operation can be obtained by adding 5 dB(A).

3: Values are based on the following conditions: FXDQ-PB external static pressure of 10 Pa; FXDQ-NB: external static pressure of 15 Pa.

MODEL	FXMQ63PVE	FXMQ80PVE	FXMQ100PVE	FXMQ125PVE	FXMQ140PVE		
Power supply		1-phase, 220-240 V/220 V, 50 Hz					
Cooling capacity	kcal/h (*1)	6,300	8,000	10,000	12,500	14,300	
	Btu/h (*1)	24,900	31,700	39,600	49,500	57,000	
	kW	(*1)	7.3	9.3	11.6	14.5	16.7
		(*2)	7.1	9.0	11.2	14.0	16.0
Heating capacity	kcal/h	6,900	8,600	10,800	13,800	15,500	
	Btu/h	27,300	34,100	42,700	54,600	61,400	
	kW	8.0	10.0	12.5	16.0	18.0	
Casing		Galvanised steel plate					
Airflow rate (HH/H/L)	m ³ /min	19.5/17.5/16	25/22.5/20	32/27/23	39/33/28	46/39/32	
	cfm	688/618/565	883/794/706	1,130/953/812	1,377/1,165/988	1,624/1,377/1,130	
External static pressure	Pa	50-200*1	50-200*1	50-200*1	50-200*1	50-140*1	
Sound level (HH/H/L)	dB(A)	42/40/38	43/41/39	43/41/39	44/42/40	46/45/43	
Dimensions (H×W×D)	mm	300×1,000×700	300×1,000×700	300×1,400×700	300×1,400×700	300×1,400×700	
Machine weight	kg	36	36	46	46	47	
Piping connections	Liquid (Flare)	φ 9.5	φ 9.5	φ 9.5	φ 9.5	φ 9.5	
	Gas (Flare)	φ 15.9	φ 15.9	φ 15.9	φ 15.9	φ 15.9	
	Drain	VP25 (External Dia, 32/Internal Dia, 25)					

Note: Specifications are based on the following conditions;

-Cooling: Indoor temp.: (*1) 27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.

(*2) 27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.

-Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.

-Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index.

-Sound level: Anechoic chamber conversion value, measured at a point 1.5 m downward from the unit centre.

During actual operation, these values are normally somewhat higher as a result of ambient conditions.

* 1: External static pressure can be modified using a remote controller that offers seven (FXMQ20-32P), thirteen (FXMQ40P), fourteen (FXMQ50-125P) or ten (FXMQ140P) levels of control. These values indicate the lowest and highest possible static pressures. The standard static pressure is 50 Pa for FXMQ20-32P and 100 Pa for FXMQ40-140P.


SPECIFICATIONS

Ceiling Suspended Type



MODEL		FXHQ32MAVE	FXHQ63MAVE	FXHQ100MAVE	
Power supply		1-phase, 220-240 V/220 V, 50 Hz			
Cooling capacity	kcal/h (*1)	3,200	6,300	10,000	
	Btu/h (*1)	12,600	24,900	39,600	
	kW (*1)	3.7	7.3	11.6	
	(*2)	3.6	7.1	11.2	
Heating capacity	kcal/h	3,400	6,900	10,800	
	Btu/h	13,600	27,300	42,700	
	kW	4.0	8.0	12.5	
Casing		White (10Y9/0.5)			
Airflow rate (H/L)	m ³ /min	12/10	17.5/14	25/19.5	
	cfm	424/353	618/494	883/688	
Sound level (H/L)	dB(A)	36/31	39/34	45/37	
Dimensions (H×W×D)	mm	195×960×680	195×1,160×680	195×1,400×680	
Machine weight	kg	24	28	33	
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 9.5	φ 9.5
	Gas (Flare)		φ 12.7	φ 15.9	φ 15.9
	Drain		VP20 (External Dia, 26/Internal Dia, 20)		

Floor Standing Type/Concealed Floor Standing Type



MODEL		FXLQ20MAVE	FXLQ25MAVE	FXLQ32MAVE	FXLQ40MAVE	FXLQ50MAVE	FXLQ63MAVE
		FXNQ20MAVE	FXNQ25MAVE	FXNQ32MAVE	FXNQ40MAVE	FXNQ50MAVE	FXNQ63MAVE
Power supply		1-phase, 220-240 V/220 V, 50 Hz					
Cooling capacity	kcal/h (*1)	2,000	2,500	3,200	4,000	5,000	6,300
	Btu/h (*1)	7,800	9,900	12,600	16,000	19,800	24,900
	kW (*1)	2.3	2.9	3.7	4.7	5.8	7.3
	(*2)	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	kcal/h	2,200	2,800	3,400	4,300	5,400	6,900
	Btu/h	8,500	10,900	13,600	17,100	21,500	27,300
	kW	2.5	3.2	4.0	5.0	6.3	8.0
Casing		FXLQ: Ivory white (5Y7.5/1) / FXNQ: Galvanised steel plate					
Airflow rate (H/L)	m ³ /min	7/6	7/6	8/6	11/8.5	14/11	16/12
	cfm	247/212	247/212	282/212	388/300	494/388	565/424
Sound level (H/L)	220 V	dB(A)	35/32	35/32	35/32	38/33	39/34
	240 V		37/34	37/34	37/34	40/35	41/36
Dimensions (H×W×D)	FXLQ	mm	600×1,000×222	600×1,000×222	600×1,140×222	600×1,140×222	600×1,420×222
	FXNQ		610×930×220	610×930×220	610×1,070×220	610×1,070×220	610×1,350×220
Machine weight	FXLQ	kg	25	25	30	30	36
	FXNQ		19	19	23	23	27
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 6.4	φ 6.4	φ 6.4	φ 6.4
	Gas (Flare)		φ 12.7	φ 12.7	φ 12.7	φ 12.7	φ 15.9
	Drain		φ 21O.D.				

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: (*1) 27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 (*2) 27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index.
 •Sound level: Anechoic chamber conversion value, measured at a point 1.5 m in front of the unit at a height of 1.5 m.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Wall Mounted Type



MODEL		FXAQ20PVE	FXAQ25PVE	FXAQ32PVE	FXAQ40PVE	FXAQ50PVE	FXAQ63PVE
Power supply		1-phase, 220-240/220V, 50 Hz					
Cooling capacity	kcal/h (*1)	2,000	2,500	3,200	4,000	5,000	6,300
	Btu/h (*1)	7,800	9,900	12,600	16,000	19,800	24,900
	kW (*1)	2.3	2.9	3.7	4.7	5.8	7.3
	(*2)	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	kcal/h	2,200	2,800	3,400	4,300	5,400	6,900
	Btu/h	8,500	10,900	13,600	17,100	21,500	27,300
	kW	2.5	3.2	4.0	5.0	6.3	8.0
Casing		White (3.0Y8.5/0.5)					
Airflow rate (H/L)	m ³ /min	7.5/4.5	8/5	8.5/5.5	12/9	15/12	19/14
	cfm	265/159	282/177	300/194	424/318	530/424	671/494
Sound level (H/L)	dB(A)	35/31	36/31	38/31	39/34	42/37	47/41
Dimensions (H×W×D)	mm	290×795×238	290×795×238	290×795×238	290×1,050×238	290×1,050×238	290×1,050×238
Machine weight	kg	11	11	11	14	14	14
Piping connections	Liquid (Flare)	mm	φ 6.4	φ 6.4	φ 6.4	φ 6.4	φ 9.5
	Gas (Flare)		φ 12.7	φ 12.7	φ 12.7	φ 12.7	φ 15.9
	Drain		VP13 (External Dia, 18/Internal Dia, 13)				

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: (*1) 27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 (*2) 27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index.
 •Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit and 1 m downward.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS

Connection unit series indoor units

- * A type of BEV unit is necessary for each Connection unit series indoor unit.
- * If indoor units from the Connection unit series are connected within a single refrigerant system to indoor units from any other series, cooling/heating switchover will not be possible using the remote controller of the Connection unit series indoor units. However, if the remote controller of an indoor unit from the other series is set as a master remote controller, cooling/heating switchover will be possible.
- * If all indoor units are from the Connection unit series, an outdoor unit Cool/Heat selector will be needed to enable cooling/heating switchover.
- * Group control between Connection Unit series equipment within one system is possible. However, group control with the other VRV indoor units is not possible.

Ceiling Suspended Cassette Type (50 Hz only)



MODEL	Indoor unit		FXUQ71MAV1	FXUQ100MAV1	FXUQ125MAV1	
	Connection unit		BEVQ71MAVE	BEVQ100MAVE	BEVQ125MAVE	
Power supply		1-phase, 220-240 V, 50 Hz				
Cooling capacity	Kcal/h(*1)		7,100	10,000	12,500	
		Btu/h(*1)	28,300	39,600	49,500	
	kW	(*1)	8.3	11.6	14.5	
		(*2)	8.0	11.2	14.0	
Heating capacity (Max.)	Kcal/h		7,700	10,800	12,000	
	Btu/h		30,700	42,700	47,800	
	kW		9.0	12.5	14.0	
Casing		White(10Y9/0.5)				
Indoor unit	Airflow rate (H/L)	m ³ /min	19/14	29/21	32/23	
		cfm	671/494	1,024/741	1,130/812	
Indoor unit	Sound level (H/L)	230 V	dB(A)	40/35	43/38	44/39
Indoor unit	Dimensions (H×W×D)	mm	165×895×895	230×895×895	230×895×895	
Indoor unit	Machine weight	kg	25	31	31	
Piping connections	Liquid	mm	φ 9.5 (Flare)			
	Gas		φ 15.9 (Flare)			
	Drain		VP 20 (External Dia. 26/Internal Dia. 20)			

Note: Specifications are based on the following conditions;
 •Cooling: Indoor temp.: (*1) 27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 (*2) 27CDB, 19CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 •Capacity of indoor unit is only for reference. Actual capacity of indoor unit is based on the total capacity index.
 •Sound level: Anechoic chamber conversion value, measured at a point 1.5 m below the unit centre.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.

OUTDOOR UNITS

Cooling Only



MODEL		RXMQ4PVE	RXMQ5PVE	RXMQ6PVE
Power supply		1-phase, 220-230 V, 50 Hz/220 V		
Cooling capacity	Kcal/h	9,600	12,000	13,300
	Btu/h	38,200	47,700	52,900
	kW	11.2	14.0	15.5
Power consumption	kW	2.95	3.97	4.44
Capacity control	%	24 to 100		
Casing colour		Ivory white (5Y7.5/1)		
Compressor	Type	Hermetically sealed scroll type		
	Motor output	kW	2.5	3.0
Airflow rate	m ³ /min	106		
Dimensions (H x W x D)	mm	1,345 x 900 x 320		
Machine weight	kg	125		
Sound level	dB(A)	50	51	53
Operation range	CDB	-5 to 46		
Refrigerant	Type	R-410A		
	Charge	kg	4.0	
Piping connections	Liquid	φ 9.5 (Flare)		
	Gas	mm	φ 15.9 (Flare)	φ 19.1 (Brazing)

Heat Pump

MODEL		RXYMQ4PVE	RXYMQ5PVE	RXYMQ6PVE	
Power supply		1-phase, 220-230 V, 50 Hz/220 V			
Cooling capacity	Kcal/h	9,600	12,000	13,300	
	Btu/h	38,200	47,800	52,900	
	kW	11.2	14.0	15.5	
Heating capacity	Kcal/h	10,800	13,800	15,500	
	Btu/h	42,700	54,600	61,400	
	kW	12.5	16.0	18.0	
Power consumption	Cooling	kW	2.95	3.97	4.44
	Heating	kW	3.27	4.09	4.82
Capacity control	%	24 to 100			
Casing colour		Ivory white (5Y7.5/1)			
Compressor	Type	Hermetically sealed scroll type			
	Motor output	kW	2.5	3.0	3.5
Airflow rate	m ³ /min	106			
Dimensions (H x W x D)	mm	1,345 x 900 x 320			
Machine weight	kg	125			
Sound level (Cooling/Heating)	dB(A)	50/52	51/53	53/55	
Operation range	Cooling	CDB	-5 to 46		
	Heating	CWB	-20 to 15.5		
Refrigerant	Type	R-410A			
	Charge	kg	4.0		
Piping connections	Liquid	φ 9.5 (Flare)			
	Gas	mm	φ 15.9 (Flare)	φ 19.1 (Brazing)	

Note: Specifications are based on the following conditions;
 • Cooling: Indoor temp.: 27CDB, 19.5CWB, Outdoor temp.: 35CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 • Heating: Indoor temp.: 20CDB, Outdoor temp.: 7CDB, 6CWB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 • Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m. During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 • Refrigerant charge is required.

OPTION LIST

INDOOR UNITS

Ceiling Mounted Cassette (Round Flow) Type

No.	Item	Type	FXFQ25L	FXFQ32L	FXFQ40L	FXFQ50L	FXFQ63L	FXFQ80L	FXFQ100L	FXFQ125L	
1	Decoration Panel						BYCP125K-W1				
2	Sealing member of air discharge outlet						KDBH55K160F				
3	Panel spacer						KDBP55H160FA				
4	Filter related	High efficiency filter unit 65%				KAFP556B80			KAFP556B160		
		High efficiency filter unit 90%				KAFP557B80			KAFP557B160		
		Replacement high efficiency filter 65%				KAFP552B80			KAFP552B160		
		Replacement high efficiency filter 90%				KAFP553B80			KAFP553B160		
		Filter chamber						KDDPF55B160			
		Long life replacement filter Non-woven type						KAFP551K160			
		Ultra long-life filter						KAFP55B160			
5	Fresh air intake kit	Replacement ultra long-life filter					KAFP55H160H				
		Chamber type Without T shape and fan						KDDP55B160			
		With T shape without fan							KDDP55B160K		
		Direct installation type							KDDP55X160		
6	Branch duct chamber						KDJP55B80		KDJP55B160		
7	Chamber connection kit								KKSJ55KA160		
8	Insulation kit for high humidity								KDTP55K80	KDTP55K160	

Ceiling Mounted Cassette (Compact Multi Flow) Type

No.	Item	Type	FXZQ20M	FXZQ25M	FXZQ32M	FXZQ40M	FXZQ50M
1	Decoration panel						BYFQ60B8W1
2	Sealing member of air discharge outlet						KDBH44BA60
3	Panel spacer						KDBQ44BA60A
4	Replacement long-life filter						KAFQ441BA60
5	Fresh air intake kit	Direct installation type					KDDQ44XA60

Ceiling Mounted Cassette (Double Flow) Type

No.	Item	Type	FXCQ20M FXCQ25M FXCQ32M	FXCQ40M	FXCQ50M	FXCQ63M	FXCQ80M	FXCQ125M
1	Decoration Panel		BYBC32G-W1	BYBC50G-W1	BYBC63G-W1	BYBC125G-W1		
2	Filter related	High efficiency filter 65% *1	KAFJ532G36	KAFJ532G56	KAFJ532G80	KAFJ532G160		
		High efficiency filter 90% *1	KAFJ533G36	KAFJ533G56	KAFJ533G80	KAFJ533G160		
		Filter chamber bottom suction	KDDFJ53G36	KDDFJ53G56	KDDFJ53G80	KDDFJ53G160		
		Long life replacement filter	KAFJ531G36	KAFJ531G56	KAFJ531G80	KAFJ531G160		

Note: *1 Filter chamber is required if installing high efficiency filter.

Ceiling Mounted Cassette Corner Type

No.	Item	Type	FXKQ25MA	FXKQ32MA	FXKQ40MA	FXKQ63MA
1	Panel related	Decoration Panel		BYK45FJW1		BYK71FJW1
		Panel Spacer		KPB52F56W		KPB52F80W
2	Air inlet and air discharge outlet related	Long life replacement filter		KAFJ521F56		KAFJ521F80
		Air discharge grille		K-HV7AW		K-HV9AW
		Air discharge blind panel		KDBJ52F56W		KDBJ52F80W
		Flexible duct (with shutter)		KFDJ52FA56		KFDJ52FA80

Slim Ceiling Mounted Duct Type (700 mm width type)

No.	Item	Type	FXDQ20PB	FXDQ25PB	FXDQ32PB
1	Insulation kit for high humidity				KDT25N32

Slim Ceiling Mounted Duct Type (900/1,100 mm width type)

No.	Item	Type	FXDQ40NB	FXDQ50NB	FXDQ63NB
1	Insulation kit for high humidity				KDT25N50

Ceiling Mounted Duct Type

No.	Item	Type	FXMQ20P FXMQ25P FXMQ32P	FXMQ40P	FXMQ50P FXMQ63P FXMQ80P	FXMQ100P FXMQ125P FXMQ140P
1	High efficiency filter	65%	KAF372AA36	KAF372AA56	KAF372AA80	KAF372AA160
		90%	KAF373AA36	KAF373AA56	KAF373AA80	KAF373AA160
2	Filter chamber		KDDF37AA36	KDDF37AA56	KDDF37AA80	KDDF37AA160
3	Long life replacement filter		KAF371AA36	KAF371AA56	KAF371AA80	KAF371AA160
4	Long life filter chamber kit		KAF375AA36	KAF375AA56	KAF375AA80	KAF375AA160
5	Service panel	White	KTBJ25K36W	KTBJ25K56W	KTBJ25K80W	KTBJ25K160W
		Fresh white	KTBJ25K36F	KTBJ25K56F	KTBJ25K80F	KTBJ25K160F
		Brown	KTBJ25K36T	KTBJ25K56T	KTBJ25K80T	KTBJ25K160T
6	Air discharge adaptor		KDAJ25K36A	KDAJ25K56A	KDAJ25K71A	KDAJ25K140A

Ceiling Suspended Type

No.	Item	Type	FXHQ32MA	FXHQ63MA	FXHQ100MA
1	Drain pump kit		KDU50N60VE		KDU50N125VE
2	Replacement long-life filter (Resin net)		KAF501DA56	KAF501DA80	KAF501DA112
3	L-type piping kit (for upward direction)		KHFP5MA63		KHFP5MA160

Wall Mounted Type

No.	Item	Type	FXAQ20P	FXAQ25P	FXAQ32P	FXAQ40P	FXAQ50P	FXAQ63P
1	Drain pump kit							K-KDU572EVE

Floor Standing Type

No.	Item	Type	FXLQ20MA	FXLQ25MA	FXLQ32MA	FXLQ40MA	FXLQ50MA	FXLQ63MA
1	Long life replacement filter		KAFJ361K28		KAFJ361K45			KAFJ361K71

Concealed Floor Standing Type

No.	Item	Type	FXNQ20MA	FXNQ25MA	FXNQ32MA	FXNQ40MA	FXNQ50MA	FXNQ63MA
1	Long life replacement filter		KAFJ361K28		KAFJ361K45			KAFJ361K71

Ceiling Suspended Cassette Type

No.	Item	Type	FXUQ71MA	FXUQ100MA	FXUQ125MA
1	Replacement long-life filter				KAF495FA140
2	Sealing member of air discharge outlet (*1)		KDBH49FA80		KDBH49FA140
3	Decoration panel for air discharge		KDBT49FA80		KDBT49FA140
4	Vertical flap kit		KDGJ49FA80		KDGJ49FA140
5	L-shape piping kit				KHFP49MA140

Note: (*1): This option is necessary for setting up 2-way (opposing directional) airflow when the air conditioner is installed.

OPTION LIST

OUTDOOR UNITS

Cooling only

No.	Item	Type	RXMQ4P	RXMQ5P	RXMQ6P
1	Cool/Heat Selector			KRC19-26A	
1-1	Fixing Box			KJB111A	
2	REFNET Header			KHRP26M22H (Max. 4 branch)	
				KHRP26M33H (Max. 8 branch)	
3	REFNET Joint			KHRP26A22T	
4	Central drain plug			KKPJ5F180	
5	Fixture for preventing overturning			KPT-60B160	
6	Wire fixture for preventing overturning			K-KYZP15C	

Heat pump

No.	Item	Type	RXYMQ4P	RXYMQ5P	RXYMQ6P
1	Cool/Heat Selector			KRC19-26A	
1-1	Fixing Box			KJB111A	
2	Cool/Heat Selector			KHRP26M22H (Max. 4 branch)	
				KHRP26M33H (Max. 8 branch)	
3	REFNET Joint			KHRP26A22T	
4	Central drain plug			KKPJ5F180	
5	Fixture for preventing overturning			KPT-60B160	
6	Wire fixture for preventing overturning			K-KYZP15C	

CONTROL SYSTEMS

Operation Control System Optional Accessories

No.	Item	Type	FXQ-L	FXQ-M	FXQ-M	FXQ-MA	FXDQ-PB FXDQ-NB	FXMQ-L	FXHQ-MA	FXAQ-L	FXLQ-MA FXNQ-MA	FXUQ-MA
1	Remote controller	Wireless	C/O	BRC7F635F	BRC7E531W	BRC7C67	BRC4C63	BRC4C66	BRC4C66	BRC7EA619	BRC4C64	BRC7CA529W
			H/P	BRC7F634F	BRC7E530W	BRC7C62	BRC4C61	BRC4C65	BRC4C65	BRC7EA63W	BRC4C62	BRC7CA528W
		Wired		BRC1C62								
2	Navigation remote controller (Wired remote controller)		BRC1E61									
3	Wired remote controller with weekly schedule timer		BRC1D61									
4	Simplified remote controller (Exposed type)						BRC2C51				BRC2C51	
5	Remote controller for hotel use (Concealed type)						BRC3A61				BRC3A61	
6	Adaptor for wiring		★KRP1C63	★KRP1B57	★KRP1B61	KRP1B61	★KRP1B56	★KRP1C64	KRP1BA54		KRP1B61	
7-1	Wiring adaptor for electrical appendices (1)		★KRP2A62	★KRP2A62	★KRP2A61	KRP2A61	★KRP2A53	★KRP2A61	★KRP2A62	★KRP2A61	KRP2A61	
7-2	Wiring adaptor for electrical appendices (2)		★KRP4AA53	★KRP4AA53	★KRP4AA51	KRP4AA51	★KRP4AA54	★KRP4AA51	★KRP4AA52	★KRP4AA51	KRP4AA51	★KRP4AA53
8	Remote sensor (for indoor temperature)		KRCS01-4B	KRCS01-1B			KRCS01-4B	KRCS01-1B				
9	Installation box for adaptor PCB		Note 2.3 KRP1H98	Note 4.6 KRP1BA101	Note 2.3 KRP1B96		Note 4.6 KRP1BA101	Note 2.3 KRP4A96	Note 3 KRP1CA93	Note 2.3 KRP4AA93		KRP1BA97
10	External control adaptor for outdoor unit		★DTA104A62	★DTA104A62	★DTA104A61	DTA104A61	★DTA104A53	★DTA104A61	★DTA104A62	★DTA104A61	DTA104A61	
11	Adaptor for multi tenant		★DTA114A61				★DTA114A61			★DTA114A61		

Note: 1. Installation box ★ is necessary for each adaptor marked ★.
2. Up to 2 adaptors can be fixed for each installation box.

3. Only one installation box can be installed for each indoor unit.
4. Up to 2 installation boxes can be installed for each indoor unit.

5. Installation box ★ is necessary for second adaptor.
6. Installation box ★ is necessary for each adaptor.

CONTROL SYSTEMS

System Configuration

No.	Item	Model No.	Function
1	Residential central remote controller	Note 3 DCS303A51	•Up to 16 groups of indoor units (128 units) can be easily controlled using the large LCD panel. ON/OFF, temperature settings and scheduling can be controlled individually for indoor units.
2	Central remote controller	Note 2 DCS302CA61	•Up to 64 groups of indoor units (128 units) can be connected, and ON/OFF, temperature setting and monitoring can be accomplished individually or simultaneously. Connectable up to 2 controllers in one system.
2-1	Electrical box with earth terminal (3 blocks)	KJB311AA	
3	Unified ON/OFF controller	Note 2 DCS301BA61	•Up to 16 groups of indoor units (128 units) can be turned, ON/OFF individually or simultaneously, and operation and malfunction can be displayed. Can be used in combination with up to 8 controllers.
3-1	Electrical box with earth terminal (2 blocks)	KJB212AA	
3-2	Noise filter (for electromagnetic interface use only)	KEK26-1A	
4	Schedule timer	Note 2 DST301BA61	•Programmed time weekly schedule can be controlled by unified control for up to 64 groups of indoor units (128 units). Can turn units ON/OFF twice per day.
5	Interface adaptor for SkyAir-series	For SkyAir, FDYJM-FA, FDY-KA, FDYB-KA, FVY(P)-A, FXUQ-MA ★ DTA102A52	•Adaptors required to connect products other than those of the VRV System to the high-speed DIII-NET communication system adopted for the VRV System. * To use any of the above optional controllers, an appropriate adaptor must be installed on the product unit to be controlled.
6	Central control adaptor kit	For UAT(Y)-K(A),FD-K ★ DTA107A55	
7	Wiring adaptor for other air-conditioner	★ DTA103A51	
8	DIII-NET Expander Adaptor	DTA109A51	•Up to 1024 units can be centrally controlled in 64 different groups. •Wiring restrictions (max. length: 1,000 m, total wiring length: 2,000 m, max. number of branches: 16) apply to each adaptor.
8-1	Mounting plate	KRP4A92	•Fixing plate for DTA109A51

Notes: 1. Installation box for ★ adaptor must be obtained locally.
2. For FXUQ-MAV1, an interface adaptor (DTA102A52) for the SkyAir series is necessary.
3. For residential use only. Cannot be used with other centralised control equipment.

Building Management System

No.	Item	Model No.	Function				
1	intelligent Touch Controller	Basic	Hardware	intelligent Touch Controller	DCS601C51	•Air-Conditioning management system that can be controlled by a compact all-in-one unit.	
		Option	Hardware	DIII-NET plus adaptor	DCS601A52		•Additional 64 groups (10 outside units) is possible.
1-2	Electrical box with earth terminal (4 blocks)			KJB411A	•Wall embedded switch box.		
2	intelligent Touch Manager	Basic	Hardware	intelligent Touch Manager	DCM601A51	•Air-conditioning management system that can be controlled by touch screen.	
		Option	Hardware	ITM plus adaptor	DCM601A52		•Additional 64 groups (10 outdoor units) is possible. Max. 7 ITM plus adaptors can be connected to intelligent Touch Manager.
				ITM integrator	DCM601A53		•Max. 5 intelligent Touch Managers can be integrated.
		Software	ITM power proportional distribution	DCM002A51	•Power consumption of indoor units are calculated based on operation status of the indoor unit and outside unit power consumption measured by kWh metre.		
2-4		Software	ITM energy navigator	DCM008A51	•Building energy consumption is visualised. Wasted air-conditioning energy can be found out.		
2-5	Di unit			DEC101A51	•8 pairs based on a pair of On/Off input and abnormality input.		
2-6	Dio unit			DEC102A51	•4 pairs based on a pair of On/Off input and abnormality input.		
3	Communication line	*1 Interface for use in BACnet*		DMS502B51	•Interface unit to allow communications between VRV and BMS. Operation and monitoring of air-conditioning systems through BACnet® communication.		
3-1		Optional DIII board	DAM411B51	•Expansion kit, installed on DMS502B51, to provide 2 more DIII-NET communication ports. Not usable independently.			
3-2		Optional Di board	DAM412B51	•Expansion kit, installed on DMS502B51, to provide 16 more wattmeter pulse input points. Not usable independently.			
4		*2 Interface for use in LONWORKS*		DMS504B51	•Interface unit to allow communications between VRV and BMS. Operation and monitoring of air-conditioning systems through LONWORKS® communication.		
5	Contact/analogue signal	Unification adaptor for computerised control		★ DCS302A52	•Interface between the central monitoring board and central control units.		

Notes: *1. BACnet® is a registered trademark of American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE).
*2. LONWORKS® is a trademark of Echelon Corporation registered in the United States and other countries.
*3. Installation box for ★ adaptor must be obtained locally.

MEMO

