

Model Name	Indoor Unit		
	Outdoor Unit		
Capacity	Cooling	Rated (Min.-Max)	Kw
	Heating	Rated (Min.-Max)	Kw
Power Supply			
Power supply connection			
Running Current	Cooling	Rated	A
	Heating		
Power consumption	Cooling	Rated	W
	Heating	(Min.-Max)	
COP	Cooling	Rated	W/W
	Heating		
Indoor Unit			
Front panel Colour			
Airflow rate (H)	Cooling	m ³ /min	
	Heating		
Fan speed			
Sound Levels (H/M/L/SL)	Cooling	dB (A)	
	Heating		
Dimensions (HxWxD)		mm	
Packaged Dimensions (H×W×D)		mm	
Machine weight		Kg	
Outdoor Unit			
Casing colour			
Compressor	Type		
Sound Levels (H/SL)	Cooling	dB (A)	
	Heating		
Dimensions (HxWxD)		mm	
Packaged Dimensions (H×W×D)		mm	
Machine weight		Kg	
Operation Range	Cooling	°CDB	
	Heating	°CWB	
Max. piping length		m	
Max. height difference		m	

Measurement conditions:

1. Cooling capacity is based on: indoor temp. 27° CDB, 19° CWB; outdoor temp. 35° CDB, 24° CWB; piping length 7.5 m.
2. Heating capacity is based on: indoor temp. 20° CDB; outdoor temp. 7° CDB, 6° CWB; piping length 7.5 m.
3. Sound levels are based on temperature conditions 1. and 2. above with 5m piping length. These are anechoic conversion values. These values are normally somewhat higher during actual operation as a result of ambient conditions.

Cooling and heating capacities above are rounded off to first decimal. 1TR (Ton of Refrigeration) = ~3.517 kiloWatt.

For the complete feature list please refer pages 39-42.

FTXS25EVMA	FTXS35EVMA	FTXS50FVMA	FTXS60FVMA	FTXS71FVMA
RXS25EBVMA	RXS35EBVMA	RXS50FVMA	RXS60FVMA	RXS71FVMA
2.5 (1.2-3.0)	3.5 (1.2-3.8)	5.0 (1.7-6.0)	6.0 (1.7-6.7)	7.1 (2.3-8.5)
3.4 (1.2-4.5)	4.0 (1.2-5.0)	5.8 (1.7-7.7)	7.0 (1.7-8.0)	8.2 (2.3-10.0)
1 phase, 230 V, 50Hz				
Outdoor unit				
3.3	4.7	6.9	8.8	10.4
4.1	4.9	7.1	9	11.1
600 (300-800)	1,020 (300-1,200)	1,550 (440-2,080)	1,980 (440-2,390)	2,360 (570-3,200)
830 (290-1,340)	1,080 (290-1,550)	1,600 (400-2,530)	2,040 (400-2,810)	2,520 (520-3,730)
4.17	3.43	3.23	3.03	3.01
4.10	3.70	3.63	3.43	3.25
FTXS25	FTXS35	FTXS50	FTXS60	FTXS71
White				
307	314	519	572	614
332	342	572	614	759
5 steps, quiet and automatic				
37 / 31 / 25 / 22	38 / 32 / 26 / 23	44 / 40 / 35 / 32	45 / 41 / 36 / 33	46 / 42 / 37 / 34
37 / 33 / 28 / 25	38 / 34 / 29 / 26	42 / 38 / 33 / 30	44 / 40 / 35 / 32	46 / 42 / 37 / 34
283 x 800 x 195	283 x 800 x 195	290 x 1,050 x 238	290 x 1,050 x 238	290 x 1,050 x 238
265×855×340	265×855×340	337×1,147×366	337×1,147×366	337×1,147×366
9			12	
RXS25	RXS35	RXS50	RXS60	RXS71
White				
Hermetically sealed swing type				
46 / 43	47 / 44		49 / 46	52 / 49
47 / 44	48 / 45		49 / 46	52 / 49
550×765×285	550×765×285	735×825×300	735×825×300	770×900×320
589×882×363	589×882×363	792×960×390	792×960×390	900×925×390
34		48		71
10 to 46				
-10 to 20			-15 to 18	
20			30	
15			20	